

# Cosmic Ice

## (January)

Designed by Susan Kazarian



### Swarovski Elements:

PRODUCT GROUP	ARTICLE NO.	AMOUNT	SIZE	COLOR	COLOR CODE
<b>CRYSTAL VERSION:</b>					
Rivets	53001	5	SS29	Blk diamond	215
Cosmic Ring	4139	1	30mm	Crystal	001
<b>JET VERSION:</b>					
Rivets	53001	2	SS29	Jet	280
Cosmic Ring	4139	1	30mm	Jet	280

### Supplies

1 pc	12mm beaded spacer large hole TierraCast® 94-5691-12
1 pc	½" distressed slide with loop TierraCast® 94-3160-40
1 pc	4mm compression rivet TierraCast® 01-0060-11
1 pc	½" x 10" strap – antique silver TierraCast® 21-0010-20
1 pc	16g jump ring TierraCast® 01-0020-01
1 pc	Large D-ring bar TierraCast® 94-6187-61 (as seen on Jet version)
1 pc	¾" Annie's toggle TierraCast® 94-6160-12 (bar only – as seen on Crystal version)
Tools	<ul style="list-style-type: none"> <li>• Crystal applicator tool (<a href="http://www.jewelrythings.com">www.jewelrythings.com</a>)</li> <li>• Revolving leather punch</li> <li>• Hardware store hammer</li> <li>• Steel block</li> </ul>

# Cosmic Ice

## (January)

Designed by Susan Kazarian



### Instructions

- **Step 1:** Using the leather strap, ~1.5" from one end of the leather, make a hole in the center using the revolving leather punch using the smallest diameter setting.
- **Step 2:** Using the Crystal applicator tool, rivet (1) crystal rivet art. 53001 in black diamond through the 12mm beaded spacer through the hole made in step 1.  
*Note: make sure to use enough pressure so the rivet holds in place.*
- **Step 3:** From the rivet side of the leather, fold the leather through (1) Art. 4139 30mm in Crystal Cosmic ring. Note: the crystal rivet should be sitting just about ¼" from the inside edge of the Cosmic ring.
- **Step 4:** While holding the leather in place: punch a hole through both pieces of leather approximately ¼" from the opposite end of the rivet. Note: see photo for proper placement
- **Step 5:** Using (1) 4mm compression rivet set, insert the nail head side through the top of the leather and the back through the wrong side of the leather. *Note: the top and the bottom of the compression rivet should snap in place. Rivet in place using your hammer and block.*

*Note: see [www.tierracast.com](http://www.tierracast.com) for instructions on how to use their rivets*

- **Step 6:** Using the leather punch, center another hole ~1" from the compression rivet in step 5. Make two additional holes ~1/2" from the hole just created.
- **Step 7:** Using (3) crystal rivet Art. 53000 in black diamond and the Crystal applicator tool, attach a rivet in each of the three holes created in step 6.
- **Step 8:** Slip the open end of the leather through the ½" distressed slide w/loop and fold the leather end on the wrong side. Note: at this point measure the bracelet for fit and adjust the leather length accordingly
- **Step 9:** Holding the leather together, punch a hole in the center of both pieces of leather.
- **Step 10:** Using (1) crystal rivet Art. 53000 in black diamond and the Crystal applicator tool, attach a rivet to both sides of the leather.
- **Step 11:** Attach the jump ring to the loop on the distressed slide and to the loop on the bar of the Annie's toggle.

*Note: For the Jet crystal version, eliminate steps 6 and 7 and use the large D-ring bar for the closure.*